

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
4 March 2004 (04.03.2004)

PCT

(10) International Publication Number
WO 2004/018902 A1

(51) International Patent Classification⁷: **F16H 55/06**
(21) International Application Number:
PCT/CZ2003/000048

(22) International Filing Date: 25 August 2003 (25.08.2003)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
PV 2002-2897 26 August 2002 (26.08.2002) CZ

(71) Applicant (for all designated States except US): SUPER-
SPROX, a.s. [CZ/CZ]; Pobebradská 28, 190 00 Praha 9
(CZ).

(72) Inventor; and

(75) Inventor/Applicant (for US only): ANDEL, Tomáš
[CZ/CZ]; Riegrova 373, 252 19 Rudná (CZ).

(74) Agent: WALTER, Jirí; Pocernická 54, 108 00 Praha 10
(CZ).

(81) Designated States (national): AU, BR, BY, CA, CN, HR,
ID, IN, JP, KR, LK, LT, LV, MX, NO, NZ, PL, RU, SG, SK
(utility model), SK, UA, US, ZA.

(84) Designated States (regional): ARIPO patent (GH, GM,
KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW),
Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),
European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE,
ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO,
SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM,
GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Declarations under Rule 4.17:


- as to applicant's entitlement to apply for and be granted
a patent (Rule 4.17(ii)) for the following designations AU,
BR, BY, CA, CN, HR, ID, IN, JP, KR, LK, LT, LV, MX, NO,
NZ, PL, RU, SG, SK, UA, ZA, ARIPO patent (GH, GM,
KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian
patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European
patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR,
GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR),
OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW,
ML, MR, NE, SN, TD, TG)
- of inventorship (Rule 4.17(iv)) for US only

Published:

- with international search report

[Continued on next page]

(54) Title: LIGHTWEIGHT SPROCKET



(57) Abstract: The present invention relates to lightweight sprocket, consisting of a central portion (1) made from light metal alloy, to which a peripheral toothed portion (2) made from ferrous alloy is joined, using rivets (3) for joining said portions (1,2), where said joining is created between radial beams (21) of the peripheral toothed portion (2) and pocket-like recess (13) in the central portion (1), radial beams (21) being overlapped across bottoms of pocket-like recesses (13), and where a thickness of radial beams (21), at least over the joining area, is decreased by 10 to 60%, in relation to full thickness of said toothed peripheral portion (2), and a thickness of a bottom of the pocket-like recess (13) in the central portion (1) is decreased by 20 to 70%, in relation to full thickness of the central portion (1) of the sprocket.